

Technical Data Sheet

Description

DSL SAE 5W20 Motor Oil is a premium quality multi-viscosity lubricant designed to meet the latest manufacturers' requirements of API SM. DSL SAE 5W20 Motor Oil meets ILSAC GF-4 requirements for use in passenger car engines. DSL SAE 5W20 Motor Oil is a premium synthetic blend motor oil.

Performance Features

- * Excellent Fuel Economy
- * Excellent volatility for low oil consumption
- * Excellent anti-wear, anti-foam and anti-rust properties
- * Excellent protection from deposits at all operations temperatures
- * Excellent cold-cranking capabilities

Applications

- * CI-4 PLUS, CI-4, CH-4/SL
 - * Mack EO-N Premium Plus '03,
 - * Cummins engines CES Engines requiring an API service SM, SL, SJ, SH, SG, SF, SE, SD and SC oils are required
- Energy conserving motor oil
ILSAC GF-4
Meets both domestic and foreign car manufacturers' requirements 20078
* Detroit Diesel Power Guard 93K214 specification

Properties

Product Specifications

Product Code	<u>SL520</u>
SAE Grade	5W20
API Rating	SM
Viscosity	
cSt @ 40°C	49.5
cSt @ 100°C	8.6
Viscosity Index	156
Pour Point, °F	-49
API Service	SM
API Energy Conserving	Yes
ILSAC Certification GF-4	Yes