



Heavy Duty 15W40 CJ-4

Technical Data Sheet

Description

DSL Super HD 15W40 CJ-4 is a premium quality engine oil specifically engineered to meet the stringent performance requirements of API CJ-4 service category for 2007 diesel engines. Formulated with the highest quality state-of-the-art additive technology, **DSL Super HD 15W40 CJ-4** exhibits excellent performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and After treatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). **DSL Super HD 15W40 CJ-4** is fully backwards compatible for use older diesel engines where API CI-4 PLUS, CI-4, CH-4, CG-4 or CF-4 oils are recommended.

Performance Features

- ✓ Outstanding Soot Control
- ✓ Outstanding thermal and oxidative stability
- ✓ Excellent High Temperature Characteristics
- ✓ Extends Engine Life
- ✓ Excellent Wear Protection
- ✓ Mixed Fleet Operations

Properties

	<u>15W40</u>
Viscosity	cSt @ 40°C 119.5
	cSt @ 100°C 16.1
Viscosity Index	146
Flash Point, °F	410
Pour Point, °F	-25
TBN	9.5
Sulfated Ash, ASTM D 874, %m	0.95
Color, ASTM D 1500	L3.5
CCS Viscosity at -20°C, ASTM D 5293, cP	6600