

Technical Data Sheet

Description

DSL Multipurpose Automatic Transmission Fluid is specially formulated for use in all automatic transmissions where either Dexron IIIH, Dexron III, Dexron IIE, Dexron II, Dexron or Mercon fluids are specified.

Features

- * Long service life
- * Long drain service
- * Excellent wear protection
- * Protects against rust, corrosion and varnish
- * Smooth and quiet shifting
- * Eliminates transmission noise and vibration
- * Excellent oxidation resistance
- * Non-foaming
- * Extends seal life
- * Superior cold temperature performance
- * Extends transmission life

Application

All North American cars and trucks that specify General Motors Dexron IIIH, Dexron III, Dexron IIE, Dexron II, Type A Suffix A, and Ford Mercon, CJ and H Automatic Transmission Fluid Recommended for power shift transmissions specifying Allison C-3/C-4 or CAT to-2 Fluids Mobil equipment hydraulics

Properties

Typical Specifications

Product Code	<u>SL1505</u>
Gravity, ° API	31.5
Viscosity	
cST @ 40°C	34.0
cST @ 100°C	7.3
cP, @ -40°C	15500
cP, @ -20°C	1250
Viscosity Index	192
Flash Point, (COC) °F	363
Pour Point, (COC) °F	-48
Color	Red