

Technical Data Sheet

Description

DSL Tractor Hydraulic Fluid is a multi-functional hydraulic fluid designed to lubricate the common sump hydraulic/transmission/final drive systems found in modern farm equipment.

Features

Good all season performance
Long fluid life
Excellent extreme pressure performance
Good filterability

Excellent anti-wear protection
Minimizes brake chatter without reducing brake capacity
Non-Foaming
Excellent corrosion protection

Performance Approvals

- John Deere: J20A, J20B, J20C, J20D, J14C, J21A
- Ford New Holland: M2C41B, M2C48B, M2C48C, M2C86B, M2C134D
- Massey-Ferguson: M1110, M1127A, M1127B, M1129A, M1135, M1139, M1141
- J.I. Case: MS1204 (JIC185), MS1205, MS1206, MS1207, MS1210 (JIC145)
- Kubota: B6 (UDT)
- White Farm: Q1826
- IHC: B6
- Allison: C-4, C-3
- Caterpillar: TO-2
- Deutz-Allis: (PF821XL)
- Versatile: (23M or 24M0)
- Landini
- Fiat-Hesson

Application

Farm equipment
Construction equipment
Off highway
Industrial tractors

Hydraulic Manufacturers

Denison HF-0, HF-1, HF-2, Eaton Hydraulics, Vickers I-2986-S, M2950-S, Sauer-Sunstrand Hydraulics

Properties

Typical Specifications

Product Code	<u>SL1503</u>
Viscosity Index	145
Viscosity	
cST @ 40°C	58.0
cST @ 100°C	9.4
Gravity, API	29.0
Flash Point (COC) °F	400
Pour Point, °F	-35
Foam Test	pass
Ash, Sulfted, wt %	1.2